

# 1550

## Straight nipple female/female



The brass generic fittings are suitable for domestic and commercial plumbing, industrial, agricultural application and generally with every non aggressive fluid.

### TECHNICAL SPECIFICATIONS

Maximum temperature: 200 °C

Minimum temperature: - 20°C (provided that the fluid remains in the liquid phase)

Maximum operating pressure: 30 bar

Threads: female UNI ISO 228

### CONSTRUCTION SPECIFICATIONS

Body : EN12165 brass

### PRODUCTION RANGE

Art.	Code		Finishing
1550	1500692	1/4"X1/4"	-
	1500319	3/8"X3/8"	-
	1500288	1/2"X3/8"	-
	1500034	1/2"X1/2"	-
	1500046	3/4"X1/2"	-
	1500047	3/4"X3/4"	-
	1500694	1"X3/8"	-
	1500080	1"X1/2"	-
	1500059	1"X3/4"	-
	1500032	1"X1"	-
	1500110	1"1/4X1"	-
	1500122	1"1/4X1"1/4	-
	1500131	1"1/2X1"1/2	-
	1501367	2"X1"	-
	1500135	2"X2"	-
	1500386	2"1/2X2"1/2	-
1500511	4"X4"	-	

### CERTIFICATIONS



### CERTIFICATIONS

