

# 1552

## Straight male/male



The brass generic fittings are suitable for domestic and commercial plumbing, industrial, agricultural application and generally with every non aggressive fluid.

### TECHNICAL SPECIFICATIONS

Maximum temperature: 200 °C

Minimum temperature: - 20°C (provided that the fluid remains in the liquid phase)

Maximum operating pressure: 30 bar

Threads: male UNI ISO 228

### CONSTRUCTION SPECIFICATIONS

Body : EN12165 brass

### PRODUCTION RANGE

Art.	Code		Finishing
1552	1500354	1/4"X1/4"	-
	1500306	3/8"X1/4"	-
	1500218	3/8"X3/8"	-
	1500395	1/2"X1/4"	-
	1500074	1/2"X3/8"	-
	1500002	1/2"X1/2"	-
	1500012	3/4"X1/2"	-
	1500008	3/4"X3/4"	-
	1500089	1"X1/2"	-
	1500022	1"X3/4"	-
	1500001	1"X1"	-
	1500044	1"1/4X1"	-
	1500025	1"1/4X1"1/4	-
	1501052	1"1/2X1"	-
	1500097	1"1/2X1"1/4	-
	1500088	1"1/2X1"1/2	-
	1500164	2"X1"1/2	-
	1500081	2"X2"	-
	1500486	2"1/2X1"1/2	-
	1500279	2"1/2X2"1/2	-
1500375	3"X3"	-	
1500487	4"X4"	-	

### CERTIFICATIONS



### CERTIFICATIONS

