

1551

Straight male/female



The brass generic fittings are suitable for domestic and commercial plumbing, industrial, agricultural application and generally with every non aggressive fluid.

TECHNICAL SPECIFICATIONS

Maximum temperature: 200 °C

Minimum temperature: - 20°C (provided that the fluid remains in the liquid phase)

Maximum operating pressure: 30 bar

Threads: male UNI ISO 228

female UNI ISO 228

CONSTRUCTION SPECIFICATIONS

Body : EN12165 brass

PRODUCTION RANGE

Art.	Code		Finishing
1551	1500861	1/4"X3/8"	-
	1500862	1/4"X1/2"	-
	1500529	3/8"X3/8"	-
	1500106	3/8"X1/2"	-
	1500581	3/8"X1"	-
	1500305	1/2"X3/8"	-
	1500259	1/2"X1/2"	-
	1500043	1/2"X3/4"	-
	1500158	1/2"X1"	-
	1501044	1/2"X24(19)	-
	1500628	24(19)X1/2"	-
	1500636	24(19)X24(19)	-
	1500140	3/4"X1/2"	-
	1500185	3/4"X3/4"	-
	1500053	3/4"X1"	-
	1500165	1"X3/4"	-
	1500272	1"X1"	-
	1500863	1"X1"1/4	-
1500864	1"1/4X1"1/2	-	

CERTIFICATIONS



CERTIFICATIONS

