

1581

Straight reducing male/female



The brass generic fittings are suitable for domestic and commercial plumbing, industrial, agricultural application and generally with every non aggressive fluid.

TECHNICAL SPECIFICATIONS

Maximum temperature: 200 °C

Minimum temperature: - 20°C (provided that the fluid remains in the liquid phase)

Maximum operating pressure: 30 bar

Threads: male UNI ISO 228

female UNI ISO 228

CONSTRUCTION SPECIFICATIONS

Body : EN12165 brass

PRODUCTION RANGE

Art.	Code		Finishing
1581	1500455	1/4"X1/8"	-
	1500380	3/8"X1/8"	-
	1500308	3/8"X1/4"	-
	1500506	1/2"X1/8"	-
	1500134	1/2"X1/4"	-
	1500093	1/2"X3/8"	-
	1500209	3/4"X3/8"	-
	1500013	3/4"X1/2"	-
	1500367	1"X1/4"	-
	1500330	1"X3/8"	-
	1500030	1"X1/2"	-
	1500016	1"X3/4"	-
	1500462	1"1/4X1/2"	-
	1500098	1"1/4X3/4"	-
	1500028	1"1/4X1"	-
	1501010	1"1/2X1/2"	-
	1500190	1"1/2X3/4"	-
	1500075	1"1/2X1"	-
	1500082	1"1/2X1"1/4	-
	1500731	2"X1"	-
	1500138	2"X1"1/4	-
	1500130	2"X1"1/2	-
	1500495	2"1/2X1"	-
1500499	2"1/2X1"1/4	-	
1500421	2"1/2X1"1/2	-	

	1500219	2"1/2X2"	-
	1500526	3"X1"1/2	-
	1500324	3"X2"	-
	1500398	3"X2"1/2	-
	1500451	4"X2"	-
	1500514	4"X2"1/2	-
	1500518	4"X3"	-

CERTIFICATIONS



CERTIFICATIONS

