

1570
T female



The brass generic fittings are suitable for domestic and commercial plumbing, industrial, agricultural application and generally with every non aggressive fluid.

TECHNICAL SPECIFICATIONS

Maximum temperature: 200 °C
 Minimum temperature: - 20°C (provided that the fluid remains in the liquid phase)
 Maximum operating pressure: 30 bar
 Threads: female UNI ISO 228

CONSTRUCTION SPECIFICATIONS

Body : EN12165 brass

PRODUCTION RANGE

Art.	Code		Finishing
1570	1500275	3/8"X3/8"X3/8"	-
	1500533	1/2"X3/8"X1/2"	-
	1500003	1/2"X1/2"X1/2"	-
	1500544	3/4"X3/8"X3/4"	-
	1500049	3/4"X1/2"X3/4"	-
	1500915	3/4"X3/4"X1/2"	-
	1500009	3/4"X3/4"X3/4"	-
	1500037	1"X1/2"X1"	-
	1500087	1"X3/4"X1"	-
	1500005	1"X1"X1"	-
	1500441	1"1/4X1/2"X1"1/4	-
	1500446	1"1/4X3/4"X1"1/4	-
	1500719	1"1/4X1"X1"1/4	-
	1500029	1"1/4X1"1/4X1"1/4	-
	1500078	1"1/2X1"1/2X1"1/2	-
	1500120	2"X2"X2"	-
1500481	4"X4"X4"	-	

CERTIFICATIONS



CERTIFICATIONS

