

1500

Roma male hose-end



The brass generic fittings are suitable for domestic and commercial plumbing, industrial, agricultural application and generally with every non aggressive fluid.

TECHNICAL SPECIFICATIONS

Maximum temperature: 200 °C

Minimum temperature: - 20°C (provided that the fluid remains in the liquid phase)

Maximum operating pressure: 30 bar

Threads: male UNI ISO 228

CONSTRUCTION SPECIFICATIONS

Body : EN12165 brass

PRODUCTION RANGE

Art.	Code		Finishing
1500	1500473	6 X 1/4"	-
	1500568	8 X 1/4"	-
	1500568	10 X 1/4"	-
	1500479	10 X 3/8"	-
	1500522	12 X 3/8"	-
	1500326	12 X 1/2"	-
	1500547	14 X 3/8"	-
	1500418	14 X 1/2"	-
	1500160	15 X 1/2"	-
	1500189	20 X 1/2"	-
	1500116	20 X 3/4"	-
	1500192	25 X 3/4"	-
	1500129	25 X 1"	-
	1500223	30 X 1"	-
	1500241	35 X 1" 1/4	-
	1500239	40 X 1" 1/2	-
	1500417	45 X 1" 1/2	-
1500215	50 X 2"	-	

CERTIFICATIONS

